

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m <sup>3</sup> /h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
HPX-35-2T-0.75										Exclude. Gas Temp> 100°C
HPX-35-4T-0.33										Exclude. Gas Temp> 100°C
HPX-45-4T-0.33										Exclude. Gas Temp> 100°C
HPX-45-4T-0.50										Exclude. Gas Temp> 100°C
HPX-50-4T-0.75										Exclude. Gas Temp> 100°C
HPX-50-4T-1 IE3										Exclude. Gas Temp> 100°C
HPX-56-4T-0.75										Exclude. Gas Temp> 100°C
HPX-56-4T-1 IE3										Exclude. Gas Temp> 100°C
HPX-56-4T-1.5 IE3										Exclude. Gas Temp> 100°C
HPX-63-4T-1.5 IE3										Exclude. Gas Temp> 100°C
HPX-63-4T-2 IE3										Exclude. Gas Temp> 100°C
HPX-71-4T-1.5 IE3										Exclude. Gas Temp> 100°C
HPX-71-4T-2 IE3										Exclude. Gas Temp> 100°C
HPX-71-4T-3 IE3										Exclude. Gas Temp> 100°C
HPX-80-4T-4 IE3										Exclude. Gas Temp> 100°C
HPX-80-4T-5.5 IE3										Exclude. Gas Temp> 100°C
HPX-90-4T-5.5 IE3										Exclude. Gas Temp> 100°C
HPX-90-4T-7.5 IE3										Exclude. Gas Temp> 100°C
HPX-100-4T-10 IE3										Exclude. Gas Temp> 100°C
HPX-100-4T-15 IE3										Exclude. Gas Temp> 100°C