

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP).

<b>MC</b>	Measurement category
<b>EC</b>	Efficiency category
<b>VSD</b>	Variable Speed Drive
<b>SR</b>	Specific ratio

<b>[m<sup>3</sup>/h]</b>	Flow rate
<b>[Pa]</b>	Static pressure or total (depending on EC)
<b>[RPM]</b>	Rotation per minute

<b>η<sub>e</sub> [%]</b>	Efficiency
<b>N</b>	Efficiency grade
<b>[kW]</b>	Input power

Model	MC	EC	VSD	SR	η <sub>e</sub> [%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
CMR-1031-2T IE3	A	Staattinen	VSD ei tarvita	1.01	57.2	66.9	1.192	2553	961	2916
CMR-1135-2T IE3	A	Staattinen	VSD ei tarvita	1.01	59.8	66.4	2.365	4249	1198	2916
CMR-1240-2T IE3	A	Staattinen	VSD ei tarvita	1.02	70.7	74.4	4.417	6744	1667	2901
CMR-1240-4T IE3	A	Staattinen	VSD ei tarvita	1.00	52.5	65.9	0.530	2924	342	1453
CMR-1445-2T IE3	A	Staattinen	VSD ei tarvita	1.02	64.9	66.0	7.766	8951	2025	2935
CMR-1445-4T IE3	A	Staattinen	VSD ei tarvita	1.01	57.3	68.1	0.932	3883	495	1468
CMR-1650-2T IE3	B	Kokonaispaine	VSD ei tarvita	1.02	69.1	69.0	11.782	12597	2327	2946
CMR-1650-4T IE3	A	Staattinen	VSD ei tarvita	1.01	61.1	69.8	1.462	5378	597	1449
CMR-1856-4T IE3	A	Staattinen	VSD ei tarvita	1.01	60.1	65.7	2.959	8342	768	1448
CMR-2063-4T IE3	B	Kokonaispaine	VSD ei tarvita	1.02	72.2	78.8	2.349	4000	1527	1486
CMR-2063-6T IE3	A	Staattinen	VSD ei tarvita	1.00	63.5	71.5	1.725	9620	410	952
CMR-2271-4T IE3	B	Kokonaispaine	VSD ei tarvita	1.01	77.0	76.9	11.853	22371	1469	1470
CMR-2271-6T IE3	B	Kokonaispaine	VSD ei tarvita	1.01	67.4	72.3	3.463	15008	560	970
CMR-2380-4T IE3	B	Kokonaispaine	VSD ei tarvita	1.02	78.5	77.8	19.351	29118	1877	1475
CMR-2380-6T IE3	B	Kokonaispaine	VSD ei tarvita	1.01	72.1	74.1	6.424	19483	855	981