

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP).

<b>MC</b>	Measurement category	<b>[m<sup>3</sup>/h]</b>	Flow rate	<b>η<sub>e</sub> [%]</b>	Efficiency
<b>EC</b>	Efficiency category	<b>[Pa]</b>	Static pressure or total (depending on EC)	<b>N</b>	Efficiency grade
<b>VSD</b>	Variable Speed Drive	<b>[RPM]</b>	Rotation per minute	<b>[kW]</b>	Input power
<b>SR</b>	Specific ratio				

Model	MC	EC	VSD	SR	η <sub>e</sub> [%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
CJPF/ATEX-1240-4T-1/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1650-4T-2/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1856-4T-4/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1856-6T-1/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1663-4T-5.5/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1663-6T-1.5/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1871-6T-3/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-2180-6T-5.5/2G Ex eb					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1240-4T-1/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1650-4T-2/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1856-4T-4/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1856-6T-1/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1663-4T-5.5/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1663-6T-1.5/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-1871-6T-3/2G Ex db					ErP: Poissuljettu. ATEX					
CJPF/ATEX-2180-6T-5.5/2G Ex db					ErP: Poissuljettu. ATEX					