

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP).

<b>MC</b>	Measurement category
<b>EC</b>	Efficiency category
<b>VSD</b>	Variable Speed Drive
<b>SR</b>	Specific ratio

<b>[m<sup>3</sup>/h]</b>	Flow rate
<b>[Pa]</b>	Static pressure or total (depending on EC)
<b>[RPM]</b>	Rotation per minute

<b>η<sub>e</sub> [%]</b>	Efficiency
<b>N</b>	Efficiency grade
<b>[kW]</b>	Input power

Model	MC	EC	VSD	SR	η <sub>e</sub> [%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
HBA-31-2T-0.75					Escluso. Temp. del gas > 100°C					
HBA-31-2M-0.75					Escluso. Temp. del gas > 100°C					
HBA-31-4T-0.37					Escluso. Temp. del gas > 100°C					
HBA-31-4M-0.37					Escluso. Temp. del gas > 100°C					
HBA-40-2T-1.5 IE3					Escluso. Temp. del gas > 100°C					
HBA-40-2M-1.5					Escluso. Temp. del gas > 100°C					
HBA-40-4T-0.5					Escluso. Temp. del gas > 100°C					
HBA-45-2T-4 IE3					Escluso. Temp. del gas > 100°C					
HBA-50-4T-1 IE3					Escluso. Temp. del gas > 100°C					
HBA-63-4T-1.5 IE3					Escluso. Temp. del gas > 100°C					
HBA-71-4T-5.5 IE3					Escluso. Temp. del gas > 100°C					
HBA-71-6T-0.75					Escluso. Temp. del gas > 100°C					
HBA-80-6T-1.5 IE3					Escluso. Temp. del gas > 100°C					
HBA-100-6T-1.5 IE3					Escluso. Temp. del gas > 100°C					