

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CBD-2525-4M 3/4 3V	A	Statisk	VFD ikke nødvendig	1.00	37.2	44.6	0.672	2476	363	1347
CBD-2828-4M 3/4 3V	A	Statisk	VFD ikke nødvendig	1.00	39.6	46.5	0.808	3137	367	1304
CBD-2828-6M 1/3 3V	A	Statisk	VFD ikke nødvendig	1.00	35.8	45.2	0.333	2282	188	876
CBD-3333-6M 1 3V	A	Statisk	VFD ikke nødvendig	1.00	37.3	44.1	0.847	4007	284	894