

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP)

|            |                      |
|------------|----------------------|
| <b>MC</b>  | Measurement category |
| <b>EC</b>  | Efficiency category  |
| <b>VSD</b> | Variable Speed Drive |
| <b>SR</b>  | Specific ratio       |

|                          |                                  |
|--------------------------|----------------------------------|
| <b>[m<sup>3</sup>/h]</b> | Flow rate                        |
| <b>[Pa]</b>              | Static pressure / Total pressure |
| <b>[RPM]</b>             | Speed                            |

|                          |                  |
|--------------------------|------------------|
| <b>η<sub>e</sub> [%]</b> | Efficiency       |
| <b>N</b>                 | Efficiency grade |
| <b>[kW]</b>              | Input power      |

| Model         | MC | EC      | VSD                | SR                          | η <sub>e</sub> [%] | N    | [kW]  | [m <sup>3</sup> /h] | [Pa] | [RPM] |
|---------------|----|---------|--------------------|-----------------------------|--------------------|------|-------|---------------------|------|-------|
| CMP-512-4M/AL |    |         |                    | ErP eksklusiver. Pe < 125 W |                    |      |       |                     |      |       |
| CMP-514-4M/AL |    |         |                    | ErP eksklusiver. Pe < 125 W |                    |      |       |                     |      |       |
| CMP-616-4M/AL |    |         |                    | ErP eksklusiver. Pe < 125 W |                    |      |       |                     |      |       |
| CMP-820-4M/AL | A  | Statisk | VFD ikke nødvendig | 1.00                        | 41.7               | 46.3 | 0.140 | 721                 | 290  | 1450  |