

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CMRH-1445-X/R-3 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1445-X/R-4 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1445-X/R-5.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1650-X/R-4 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1650-X/R-5.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1650-X/R-7.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1856-X/R-5.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1856-X/R-7.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1856-X/R-10 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2063-X/R-7.5 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2063-X/R-10 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2063-X/R-15 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2271-X/R-15 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2271-X/R-20 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2380-X/R-25 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-2380-X/R-30 IE3					Ekskluder. Gasstemperatur > 100°C					
CMRH-1445-X/R#					Ekskluder. Gasstemperatur > 100°C					
CMRH-1650-X/R#					Ekskluder. Gasstemperatur > 100°C					
CMRH-1856-X/R#					Ekskluder. Gasstemperatur > 100°C					
CMRH-2063-X/R#					Ekskluder. Gasstemperatur > 100°C					
CMRH-2271-X/R#					Ekskluder. Gasstemperatur > 100°C					
CMRH-2380-X/R#					Ekskluder. Gasstemperatur > 100°C					