

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOSILENT 100										
ErP eksklusur. Pe < 125 W										
NEOSILENT 125										
ErP eksklusur. Pe < 125 W										
NEOSILENT 150										
ErP eksklusur. Pe < 125 W										
NEOSILENT 200 3V										
ErP eksklusur. Pe < 125 W										
NEOSILENT 250	A	Statisk	VFD ikke nødvendig	1.00	31.2	50.0	0.163	750	245	2440
NEOSILENT 315	A	Statisk	VFD ikke nødvendig	1.00	38.8	54.9	0.291	1102	369	2430