

## ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SODECA, SLU	SODECA, SLU	SODECA, SLU
b) Model	KIT-AIRHOME-2H1B	KIT-AIRHOME-3H2B	KIT-AIRHOME-4H2B
c) Specific energy consumption (SEC) average climate (kWh/(m <sup>2</sup> .yr))	-36.3	-36.3	-36.3
c) Specific energy consumption (SEC) cold climate (kWh/(m <sup>2</sup> .yr))	-71.9	-71.9	-71.9
c) Specific energy consumption (SEC) warm climate (kWh/(m <sup>2</sup> .yr))	-13.2	-13.2	-13.2
c) SEC class	A	A	A
d) Typology	RVU / BVU	RVU / BVU	RVU / BVU
e) Drive type	Variabel hastighet	Variabel hastighet	Variabel hastighet
f) HRS type	Regenerativ	Regenerativ	Regenerativ
g) Thermal efficiency of heat recovery (%)	78	78	78
h) Maximum flow rate (m <sup>3</sup> /h)	200	200	200
i) Electric power input of the fan drive at maximum flow rate (W)	73	73	73
j) Sound power level (LWA) (dBA)	32	32	32
k) Reference flow rate (m <sup>3</sup> /s)	0.033	0.033	0.033
l) Reference pressure difference (Pa)	100	100	100
m) SPI (W/m <sup>3</sup> /h)	0.38	0.38	0.38
n) Control factor	0.65	0.65	0.65
n) Control typology	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll
o) Declared max. internal leakage rate (%)	2.8	2.8	2.8
o) Max. external leakage rate (%)	2.8	2.8	2.8
p) Mixing rate	0.00	0.00	0.00
q) Position and description of visual filter warning	Se manual	Se manual	Se manual
r) Instructions to install regulated grilles	Se manual	Se manual	Se manual
s) Website	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>	<a href="http://www.sodeca.com">www.sodeca.com</a>
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	400	400	400
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	300	300	300
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	900	900	900
w) Annual heating saved (AHS) average climate (kWh/yr)	4400	4400	4400
w) Annual heating saved (AHS) warm climate (kWh/yr)	2000	2000	2000
w) Annual heating saved (AHS) cold climate (kWh/yr)	8600	8600	8600
ErP compliance	2018	2018	2018