

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
HBA-31-2T-0.75										Behalve: gastemp. >100 °C
HBA-31-2M-0.75										Behalve: gastemp. >100 °C
HBA-31-4T-0.37										Behalve: gastemp. >100 °C
HBA-31-4M-0.37										Behalve: gastemp. >100 °C
HBA-40-2T-1.5 IE3										Behalve: gastemp. >100 °C
HBA-40-2M-1.5										Behalve: gastemp. >100 °C
HBA-40-4T-0.5										Behalve: gastemp. >100 °C
HBA-45-2T-4 IE3										Behalve: gastemp. >100 °C
HBA-50-4T-1 IE3										Behalve: gastemp. >100 °C
HBA-63-4T-1.5 IE3										Behalve: gastemp. >100 °C
HBA-71-4T-5.5 IE3										Behalve: gastemp. >100 °C
HBA-71-6T-0.75										Behalve: gastemp. >100 °C
HBA-80-6T-1.5 IE3										Behalve: gastemp. >100 °C
HBA-100-6T-1.5 IE3										Behalve: gastemp. >100 °C