

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

| | |
|------------|----------------------|
| MC | Measurement category |
| EC | Efficiency category |
| VSD | Variable Speed Drive |
| SR | Specific ratio |

| | |
|--------------------------|----------------------------------|
| [m³/h] | Flow rate |
| [Pa] | Static pressure / Total pressure |
| [RPM] | Speed |

| | |
|---------------|------------------|
| ηe [%] | Efficiency |
| N | Efficiency grade |
| [kW] | Input power |

| Model | MC | EC | VSD | SR | ηe[%] | N | [kW] | [m ³ /h] | [Pa] | [RPM] |
|-------------------|----|----|-----|----|-------|---|------|---------------------|------|---------------------------|
| HPX-35-2T-0.75 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-35-4T-0.33 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-45-4T-0.33 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-45-4T-0.50 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-50-4T-0.75 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-50-4T-1 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-56-4T-0.75 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-56-4T-1 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-56-4T-1.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-63-4T-1.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-63-4T-2 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-71-4T-1.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-71-4T-2 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-71-4T-3 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-80-4T-4 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-80-4T-5.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-90-4T-5.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-90-4T-7.5 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-100-4T-10 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |
| HPX-100-4T-15 IE3 | | | | | | | | | | Behalve: gastemp. >100 °C |