

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP)

<b>MC</b>	Measurement category
<b>EC</b>	Efficiency category
<b>VSD</b>	Variable Speed Drive
<b>SR</b>	Specific ratio

<b>[m<sup>3</sup>/h]</b>	Flow rate
<b>[Pa]</b>	Static pressure / Total pressure
<b>[RPM]</b>	Speed

<b>ηe [%]</b>	Efficiency
<b>N</b>	Efficiency grade
<b>[kW]</b>	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
HPX/SEC-63-4T-1 IE3										Behalve: gastemp. >100 °C
HPX/SEC-63-4T-1.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-63-4T-2 IE3										Behalve: gastemp. >100 °C
HPX/SEC-63-4T-3 IE3										Behalve: gastemp. >100 °C
HPX/SEC-63-4T-4 IE3										Behalve: gastemp. >100 °C
HPX/SEC-71-4T-1.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-71-4T-2 IE3										Behalve: gastemp. >100 °C
HPX/SEC-71-4T-3 IE3										Behalve: gastemp. >100 °C
HPX/SEC-71-4T-4 IE3										Behalve: gastemp. >100 °C
HPX/SEC-80-4T-4 IE3										Behalve: gastemp. >100 °C
HPX/SEC-80-4T-5.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-90-4T-4 IE3										Behalve: gastemp. >100 °C
HPX/SEC-90-4T-5.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-90-4T-7.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-90-4T-10 IE3										Behalve: corrosieve omgevingen
HPX/SEC-100-4T-7.5 IE3										Behalve: gastemp. >100 °C
HPX/SEC-100-4T-10 IE3										Behalve: corrosieve omgevingen
HPX/SEC-100-4T-15 IE3										Behalve: corrosieve omgevingen
HPX/SEC-100-4T-20 IE3										Behalve: gastemp. >100 °C