

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m ³ /h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CAS-L/EW242-2-0.33-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-T-D	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850
CAS-L/EW242-2-0.33-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-M-D	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850
CAS-L/EW242-2-0.33-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-T-P	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850
CAS-L/EW242-2-0.33-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-M-P	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850
CAS-L/EW242-2-0.33-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-T-K	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850
CAS-L/EW242-2-0.33-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.02	60.1	75.6	0.339	329	1991	2850
CAS-L/EW242-2-0.5-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.02	60.6	75.0	0.423	405	2048	2850
CAS-L/EW248-2-1-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.03	55.8	66.9	0.886	500	3263	2850
CAS-L/EW248-2-1.5-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.03	55.7	66.3	0.966	552	3223	2850
CAS-L/EW254-2-2-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.05	57.1	65.7	1.534	661	4436	2850
CAS-L/EW254-2-3-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.05	57.5	65.8	1.624	697	4496	2850
CAS-L/EW260-2-3-B-M-K	A	Statisch	VSD in ventilator ingebouwd	1.05	56.7	63.5	2.250	840	5139	2850