

## ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament  
Apply to fans

SODECA, S.L.U.

www.sodeca.com

### ERP: Performance at the best efficiency point (BEP)

<b>MC</b>	Measurement category
<b>EC</b>	Efficiency category
<b>VSD</b>	Variable Speed Drive
<b>SR</b>	Specific ratio

<b>[m<sup>3</sup>/h]</b>	Flowrate
<b>[Pa]</b>	Static pressure / Total pressure
<b>[RPM]</b>	Speed

<b>ηe [%]</b>	Efficiency
<b>N</b>	Efficiency grade
<b>[kW]</b>	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m <sup>3</sup> /h]	[Pa]	[RPM]
CBD-2525-4M 3/4 3V	A	Satyczne	Falownik nie wymagany	1.00	37.2	44.6	0.672	2476	363	1347
CBD-2828-4M 3/4 3V	A	Satyczne	Falownik nie wymagany	1.00	39.6	46.5	0.808	3137	367	1304
CBD-2828-6M 1/3 3V	A	Satyczne	Falownik nie wymagany	1.00	35.8	45.2	0.333	2282	188	876
CBD-3333-6M 1 3V	A	Satyczne	Falownik nie wymagany	1.00	37.3	44.1	0.847	4007	284	894