

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
HCDF-25-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-25-4M/2G Ex db										ErP: Wyłączając. ATEX
HCDF-31-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-31-4M/2G Ex db										ErP: Wyłączając. ATEX
HCDF-35-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-35-4M/2G Ex db										ErP: Wyłączając. ATEX
HCDF-40-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-45-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-50-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-56-4T/2G Ex db										ErP: Wyłączając. ATEX
HCDF-56-6T/2G Ex db										ErP: Wyłączając. ATEX