

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	[m³/h]	Flow rate	η_e [%]	Efficiency
EC	Efficiency category	[Pa]	Static pressure or total (depending on EC)	N	Efficiency grade
VSD	Variable Speed Drive	[RPM]	Rotation per minute	[kw]	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CBD/B/EC-1919-4M-1/5 IE4			Wyłączając ErP. Pe < 125 W							
CBD/B/EC-1919-6M-1/10 IE4			Wyłączając ErP. Pe < 125 W							
CBD/B/EC-2525-4M-1/2 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	50.3	59.6	0.338	1739	32	1400
CBD/B/EC-2525-4M-3/4 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	48.2	57.5	0.340	1725	31	1400
CBD/B/EC-2525-4M-1 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	49.5	59.4	0.275	1407	32	1400
CBD/B/EC-2525-6M-1/3 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	41.3	53.2	0.132	1500	12	900
CBD/B/EC-2828-4M-1 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	52.2	59.8	0.622	2442	44	1400
CBD/B/EC-2828-4M-2 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	46.8	54.1	0.691	2589	42	1400
CBD/B/EC-2828-6M-1/3 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	49.9	61.0	0.173	1618	17	900
CBD/B/EC-3333-6M-1 IE4	A	Satyczne	Falownik wbudowany w wentylator	1.00	42.4	50.6	0.505	2657	27	900