

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

www.sodeca.com

- | | | | | |
|---------------|--|---|---|--------------------------|
| b) Model | f) Thermal efficiency of heat recovery (%) | j) Face velocity at design flow rate | n) Static efficiency of fans according to (EU) 327/2011 | q) Visual filter warning |
| c) Typology | g) Nominal flowrate | k) Nominal external pressure | o1) Max. internal leakage rate | r) LWA radiated |
| d) Drive type | h) Effective electric power input | l) Internal pressure drop of ventilation components | o2) Max. external leakage rate | |
| e) HRS type | i) SFPint | m) Internal pressure drop of non-ventilation components | p) Energy performance of the filters | |

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
				%	m³/s	kW	Wm³/s	m/s	Pa	Pa	Pa	%	%	%			dBA	
CJLINE-1131-4T-F-400	NRVU / UVU	VSD nu este necesar	Nimic		0.323	0.217	230	1.30	215			32.1	2.4		Nu se aplica	Nu se aplica	65	2018
CJLINE-1235-4T-F-400	NRVU / UVU	VSD nu este necesar	Nimic		0.472	0.308	230	1.60	258			39.6	2.4		Nu se aplica	Nu se aplica	72	2018
CJLINE-1640-4T-F-400	NRVU / UVU	VSD nu este necesar	Nimic		0.703	0.520	230	1.80	376			50.9	2.4		Nu se aplica	Nu se aplica	77	2018
CJLINE/H-1650-4T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		1.431	1.581	230	2.80	529			47.9	2.4		Nu se aplica	Nu se aplica	90	2018
CJLINE-1845-4T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		1.020	0.604	230	2.00	490			82.7	2.4		Nu se aplica	Nu se aplica	81	2018
CJLINE-1845-6T-F-400	NRVU / UVU	Viteza variabila	Nimic		0.788	0.318	230	1.60	170			42.0	2.4		Nu se aplica	Nu se aplica	73	2018
CJLINE/H-1856-4T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		2.219	3.205	230	2.80	711			49.2	2.4		Nu se aplica	Nu se aplica	96	2018
CJLINE-1856-6T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		1.273	0.752	230	1.60	303			51.3	2.4		Nu se aplica	Nu se aplica	78	2018
CJLINE/H-2063-4T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		3.650	5.932	230	3.60	886			54.5	2.4		Nu se aplica	Nu se aplica	99	2018
CJLINE-2063-6T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		1.596	0.847	230	1.60	344			64.8	2.4		Nu se aplica	Nu se aplica	81	2018
CJLINE-2271-6T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		2.096	1.345	230	2.00	467			72.8	2.4		Nu se aplica	Nu se aplica	85	2018
CJLINE-2880-6T-F-400 IE3	NRVU / UVU	VSD nu este necesar	Nimic		3.171	2.655	230	2.50	626			74.7	2.4		Nu se aplica	Nu se aplica	87	2018