

## ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

[www.sodeca.com](http://www.sodeca.com)

- |               |  |   |  |
|---------------|--|---|--|
| b) Model      | f) Thermal efficiency of heat recovery (%) | j) Face velocity at design flow rate                    | n) Static efficiency of fans according to (EU) |
| c) Typology   | g) Nominal flowrate                        | k) Nominal external pressure                            | q) Visual filter warning                       |
| d) Drive type | h) Effective electric power input          | l) Internal pressure drop of ventilation components     | r) LWA radiated                                |
| e) HRS type   | i) SFPint                                  | m) Internal pressure drop of non-ventilation components | o1) Max. internal leakage rate                 |
|               |  |   | o2) Max. external leakage rate                 |
|               |  |   | p) Energy performance of the filters           |

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
			%	m³/s	kW	W/m³/s	m/s	Pa	Pa	Pa	%	%	%			dBa		
CJBD/C-1919-4M 1/5	NRVU / UVU	Viteza variabila	Nimic	0.287	0.180	230	5.86	197			33.2	2.4					69	2018
CJBD/C-2525-4M 1/2	NRVU / UVU	Viteza variabila	Nimic	0.676	0.496	230	8.56	277			40.7	2.4					77	2018
CJBD/C-2525-4M 3/4	NRVU / UVU	Viteza variabila	Nimic	0.764	0.660	230	9.67	341			40.2	2.4					81	2018
CJBD/C-2525-6M 1/5	NRVU / UVU	Viteza variabila	Nimic	0.519	0.190	230	6.57	116			34.1	2.4					70	2018
CJBD/C-2525-6M 1/3	NRVU / UVU	Viteza variabila	Nimic	0.575	0.221	230	7.28	126			34.2	2.4					72	2018
CJBD/C-2828-4M 1/2	NRVU / UVU	Viteza variabila	Nimic	0.749	0.520	230	7.88	263			44.5	2.4					76	2018
CJBD/C-2828-4M 3/4	NRVU / UVU	Viteza variabila	Nimic	0.918	0.789	230	9.66	348			40.9	2.4					81	2018
CJBD/C-2828-6M 1/3	NRVU / UVU	Viteza variabila	Nimic	0.750	0.329	230	7.89	154			38.7	2.4					72	2018
CJBD/C-3333-6T 1 1/2	NRVU / UVU	Viteza variabila	Nimic	1.423	0.997	230	10.78	294			42.9	2.4					85	2018
CJBD/C-3333-6M 3/4	NRVU / UVU	Viteza variabila	Nimic	0.847	0.660	230	6.42	307			45.9	2.4					74	2018
CJBD/C-3333-6M 1	NRVU / UVU	Viteza variabila	Nimic	1.278	0.887	230	9.68	286			42.2	2.4					81	2018
CJBD/C-3939-6T 3	NRVU / UVU	Viteza variabila	Nimic	0.780	0.967	230	4.08	518			44.2	2.4					88	2018