

**ECODESIGN INFORMATION**

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

www.sodeca.com

- b) Model
- c) Typology
- d) Drive type
- e) HRS type
- f) Thermal efficiency of heat recovery (%)
- g) Nominal flowrate
- h) Effective electric power input
- i) SFPint
- j) Face velocity at design flow rate
- k) Nominal external pressure
- l) Internal pressure drop of ventilation components
- m) Internal pressure drop of non-ventilation components
- n) Static efficiency of fans according to (EU) 327/2011
- o1) Max. internal leakage rate
- o2) Max. external leakage rate
- p) Energy performance of the filters
- q) Visual filter warning
- r) LWA radiated

| b)                 | c)         | d)               | e)    | f)    | g)    | h)  | i)     | j)  | k) | l) | m) | n)   | o1) | o2) | p)           | q)           | r)  | ERP  |
|--------------------|------------|------------------|-------|-------|-------|-----|--------|-----|----|----|----|------|-----|-----|--------------|--------------|-----|------|
|                    |            |                  |       | %     | m³/s  | kW  | W/m³/s | m/s | Pa | Pa | Pa | %    | %   | %   |              |              | dBA |      |
| CRF/EW-190-M/CPC   | NRVU / UVU | Viteza variabila | Nimic | 0.163 | 0.085 | 230 | 8.22   | 139 |    |    |    | 40.2 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-250-M/CPC   | NRVU / UVU | Viteza variabila | Nimic | 0.298 | 0.170 | 230 | 8.68   | 177 |    |    |    | 57.8 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-315-M/L/CPC | NRVU / UVU | Viteza variabila | Nimic | 0.529 | 0.146 | 230 | 6.18   | 83  |    |    |    | 65.9 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-315-M/H/CPC | NRVU / UVU | Viteza variabila | Nimic | 0.768 | 0.526 | 230 | 9.07   | 260 |    |    |    | 66.2 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-400-M/M/CPC | NRVU / UVU | Viteza variabila | Nimic | 1.208 | 0.513 | 230 | 8.58   | 161 |    |    |    | 66.7 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-400-M/H/CPC | NRVU / UVU | Viteza variabila | Nimic | 1.287 | 0.735 | 230 | 9.14   | 229 |    |    |    | 65.8 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-400-T/CPC   | NRVU / UVU | Viteza variabila | Nimic | 1.359 | 1.385 | 230 | 9.65   | 448 |    |    |    | 62.7 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-500-M/CPC   | NRVU / UVU | Viteza variabila | Nimic | 1.735 | 0.738 | 230 | 8.05   | 170 |    |    |    | 63.1 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |
| CRF/EW-500-T/L/CPC | NRVU / UVU | Viteza variabila | Nimic | 2.029 | 1.321 | 230 | 9.41   | 285 |    |    |    | 62.8 | 2.4 |     | Nu se aplica | Nu se aplica |     | 2018 |