

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m³/h]	[Pa]	[RPM]
CI-CO-50-4T	A	Static	VSD nu este necesar	1.00	42.5	61.3	1.422	6050	0	1395
CI-CO-50-4/8T	A	Static	VSD nu este necesar	1.00	42.5	61.3	1.422	6050	0	1395
CI-CO-75-4T	A	Static	VSD nu este necesar	1.00	40.0	54.6	2.537	8080	0	1450
CI-CO-75-4/8T	A	Static	VSD nu este necesar	1.00	36.2	50.1	2.803	8080	0	1450
CI-CO-100-4T	A	Static	VSD nu este necesar	1.00	56.7	70.6	2.759	9340	0	1445
CI-CO-100-4/8T	A	Static	VSD nu este necesar	1.00	47.2	59.8	3.311	9340	0	1445