

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CMP/EC-616-2M-0.75 IE5	A	Static	VSD incorporat in ventilator	1.00	44.2	60.4	0.286	639	712	2910
CMP/EC-620-2M-0.5 IE5	A	Static	VSD incorporat in ventilator	1.00	47.3	61.7	0.422	699	1026	2910
CMP/EC-718-2M-1 IE5	A	Static	VSD incorporat in ventilator	1.00	42.4	55.7	0.543	909	913	2910
CMP/EC-820-2M-1.5 IE5	A	Static	VSD incorporat in ventilator	1.00	53.1	65.9	0.597	935	1219	2910
CMP/EC-922-4M-0.75 IE5	A	Static	VSD incorporat in ventilator	1.00	46.3	63.3	0.242	1187	339	1410
CMP/EC-1025-4M-1.5 IE5	A	Static	VSD incorporat in ventilator	1.00	45.2	59.4	0.440	1519	470	1410