

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CMA/EC-426-2M-0.5 IE5	A	Static	VSD incorporat in ventilator	1.00	39.8	56.7	0.246	316	1116	2910
CMA/EC-527-2M-0.75 IE5	A	Static	VSD incorporat in ventilator	1.00	44.6	59.7	0.370	436	1364	2910
CMA/EC-528-2M-1 IE5	A	Static	VSD incorporat in ventilator	1.00	42.6	55.9	0.544	631	1323	2910
CMA/EC-531-2M-1.5 IE5	A	Static	VSD incorporat in ventilator	1.00	53.2	63.7	0.998	1173	1629	2910