

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flowrate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOSILENT 100			Не подлежит ErP. Вх. эл. мощн. < 125 Вт							
NEOSILENT 125			Не подлежит ErP. Вх. эл. мощн. < 125 Вт							
NEOSILENT 150			Не подлежит ErP. Вх. эл. мощн. < 125 Вт							
NEOSILENT 200			Не подлежит ErP. Вх. эл. мощн. < 125 Вт							
NEOSILENT 250	A	Статический	VSD не нужен	1.00	31.9	50.6	0.165	803	236	2505
NEOSILENT 315	A	Статический	VSD не нужен	1.00	34.4	50.5	0.293	1112	326	2320