

# ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU
b) Model	CTD-125/B	CTD-150/B	CTD-160/B	CTD-200/B	CTD-125/C	CTD-150/C	CTD-160/C	CTD-200/C
c) Specific energy consumption (SEC) average climate (kWh/(m <sup>2</sup> .yr))	-26.2	-26.2	-26.2	-26.8	-26.2	-26.2	-26.2	-26.8
c) Specific energy consumption (SEC) cold climate (kWh/(m <sup>2</sup> .yr))	-53.2	-53.2	-53.2	-53.8	-53.2	-53.2	-53.2	-53.8
c) Specific energy consumption (SEC) warm climate (kWh/(m <sup>2</sup> .yr))	-10.7	-10.7	-10.7	-11.3	-10.7	-10.7	-10.7	-11.3
c) SEC class	B	B	B	B	B	B	B	B
d) Typology	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU
e) Drive type	Varierande hastighet	Varierande hastighet	Varierande hastighet	Varierande hastighet	Varierande hastighet	Varierande hastighet	Varierande hastighet	Varierande hastighet
f) HRS type	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen
g) Thermal efficiency of heat recovery (%)								
h) Maximum flow rate (m <sup>3</sup> /h)	353	353	353	834	353	353	353	834
i) Electric power input of the fan drive at maximum flow rate (W)	74	74	74	126	74	74	74	126
j) Sound power level (LWA) (dBA)	61	61	61	61	61	61	61	61
k) Reference flow rate (m <sup>3</sup> /s)	0.069	0.069	0.069	0.162	0.069	0.069	0.069	0.162
l) Reference pressure difference (Pa)	50	50	50	50	50	50	50	50
m) SPI (W/m <sup>3</sup> /h)	0.162	0.162	0.162	0.117	0.162	0.162	0.162	0.117
n) Control factor	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65
n) Control typology	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll	Lokal efterfrågan kontroll
o) Declared max. internal leakage rate (%)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
o) Max. external leakage rate (%)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
p) Mixing rate	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar	Inte tillämpbar
r) Instructions to install regulated grilles	Inte tillämpbar	Se handboken	Se handboken	Se handboken	Inte tillämpbar	Se handboken	Se handboken	Se handboken
s) Website	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	100	100	100	100	100	100	100	100
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	100	100	100	100	100	100	100	100
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	100	100	100	100	100	100	100	100

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

w) Annual heating saved (AHS) average climate (kWh/yr)	2800	2800	2800	2800	2800	2800	2800	2800
w) Annual heating saved (AHS) warm climate (kWh/yr)	1300	1300	1300	1300	1300	1300	1300	1300
w) Annual heating saved (AHS) cold climate (kWh/yr)	5500	5500	5500	5500	5500	5500	5500	5500
ErP compliance	2018	2018	2018	2018	2018	2018	2018	2018