

INFORMATION OM EKODESIGN

Enligt Europeiska kommissionens förordning nr 327/2011 som tillämpar Europaparlamentets direktiv 2009/125/EG
Tillämpas på fläktar

SODECA, S.L.U.

www.sodeca.com

ERP: Prestanda vid bästa effektivitetspunkt (BEP)

MC	Måtningskategori
EC	Effektivitetskategori
VSD	Variabel hastighet
SR	Specifikt förhållande

[m³/h]	Flödeshastighet
[Pa]	Statiskt tryck/totalt tryck
[RPM]	Hastighet

ηe [%]	Effektivitet
N	Effektivitetsgrad
[kw]	Ineffekt

Modell	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CMA/ATEX-324-2T/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-325-2T/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-426-2T/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-527-2T/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-528-2T-1/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-528-2T-1.5/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-531-2T-1.5/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-531-2T-2/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-540-2T/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-545-2T-3/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-545-2T-4/2G Ex eb										ErP: Uteslut. ATEX
CMA/ATEX-324-2T/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-325-2T/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-426-2T/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-527-2T/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-528-2T-1/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-528-2T-1.5/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-531-2T-1.5/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-531-2T-2/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-540-2T/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-545-2T-3/2G Ex db										ErP: Uteslut. ATEX
CMA/ATEX-545-2T-4/2G Ex db										ErP: Uteslut. ATEX