

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure or total (depending on EC)
[RPM]	Rotation per minute

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CMPH-512-2T-0.25					Utesluta. Gastemperatur> 100 ° C					
CMPH-512-4T-0.16					Utesluta. Gastemperatur> 100 ° C					
CMPH-514-2T-0.25					Utesluta. Gastemperatur> 100 ° C					
CMPH-514-4T-0.16					Utesluta. Gastemperatur> 100 ° C					
CMPH-616-2T-0.5					Utesluta. Gastemperatur> 100 ° C					
CMPH-616-4T-0.16					Utesluta. Gastemperatur> 100 ° C					
CMPH-620-2T-0.5					Utesluta. Gastemperatur> 100 ° C					
CMPH-620-4T-0.16					Utesluta. Gastemperatur> 100 ° C					
CMPH-718-2T-1 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-718-4T-0.33					Utesluta. Gastemperatur> 100 ° C					
CMPH-820-2T-1.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-820-4T-0.33					Utesluta. Gastemperatur> 100 ° C					
CMPH-922-2T-1.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-922-2T-2 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-922-2T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-922-4T-0.75					Utesluta. Gastemperatur> 100 ° C					
CMPH-1025-2T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1025-2T-4 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1025-4T-1.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1128-2T-4 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1128-2T-5.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1128-4T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1128-6T-1 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1231-4T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1231-4T-4 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1231-4T-5.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1231-6T-2 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1435-4T-4 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1435-4T-5.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1435-4T-7.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1435-6T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1640-4T-5.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1640-4T-7.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1640-4T-10 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1640-6T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1845-4T-7.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1845-4T-10 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-1845-6T-3 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2050-4T-10 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2050-4T-15 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2050-4T-20 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2050-6T-5.5 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2563-6T-15 IE3					Utesluta. Gastemperatur> 100 ° C					
CMPH-2563-6T-25 IE3					Utesluta. Gastemperatur> 100 ° C					